

CLAIMS

What is claimed is:

1. A phase-locked loop comprising:
 - a comparator generating a control voltage depending on the phase-shift between a predetermined reference signal and a feedback signal;
 - an oscillator controlled by the control voltage, generating a plurality of phase-shifted signals of same period, one of the phase-shifted signals forming the output signal of the phase-locked loop;
 - a multiplexer capable of providing any of the phase-shifted signals to the input of a divider, the output of which forms the feedback signal; and
 - control means controlling the multiplexer to successively provide predetermined fractions of some of the phase-shifted signals, so that the divider, having a fixed predetermined dividing ratio (N), receives a signal having an average period equal to a real fraction of the period of the phase-shifted signals.
2. The phase-locked loop of claim 1 wherein the voltage-controlled oscillator generates a number n of phase-shifted signals of same period T_{out} so that the phase-shifted signal forming the output signal of the loop is ahead of each of the other phase-shifted signals by a duration equal to an integral multiple of a duration T_{out}/n , each of the phase-shifted signals consisting in a periodic pulse having a duration shorter than duration T_{out}/n .
3. The phase-locked loop of claim 2 wherein the control means is a sigma/delta modulator controlling the multiplexer so that the divider receives a signal, the average period (T_{int}) of which is equal to the sum of duration T_{out}/n multiplied by a first programmable integer M ranging between 0 and $n-1$ and of duration T_{out}/n

multiplied by a second programmable integer x coded over a number u of bits and divided by 2^u .

4. The phase-locked loop of claim 1 wherein the period of the signals generated by the oscillator depends on the control voltage.

5. The phase-locked loop of claim 1 wherein the comparator comprises:

a phase detector receiving as an input the reference signal and the feedback signal;

a charge pump coupled to the output of the phase detector, generating a current signal depending on the phase difference between the reference and feedback signals; and

a filter generating the control voltage based on the current signal.